

# 5M



*Premium*

**Ideal for Above or Below Ground**

*Polyester*

**Mining Applications**

*Single Jacket*

National 5M mine hose is a premium quality rubber lined, single jacket hose that has been MSHA approved (USMSHA No. 2G-15/1). A high quality polyester outer jacket protects an inner jacket rubber liner from wear and puncture while also helping to prevent kinking that limits flow.



**MINEHOSE**



**ALL-AMERICAN HOSE™**



FLAME RESISTANT POLYESTER SINGLE JACKET

TYPE	SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (50' Coupled)	BOWL SIZE
	IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
5M	1½"	250 (1725)	500 (3450)	750 (5170)	15 (6.8)	1¾"
	2"	250 (1725)	500 (3450)	750 (5170)	22 (10)	2½"

Operating Pressure not to Exceed 90% of Service Test Pressure.

**How to Order**

TYPE	HOSE I.D. x HOSE LENGTH	COLOR (Dura-Cote™)	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
5M	15 = 1½" x 50 = 50'	W = White (Uncoated)	15 = 1½"	N = NH	Blank = Aluminum BR = Brass Rocker Lug BP = Brass Pin Lug
	20 = 2" x 100 = 100'		20 = 2"	I = IPT	

**Part No. Example: 5M15X50W15N =**  
5M Hose, 1½" ID by 50' Length, White, 1½" Aluminum NH/NST Threaded Coupling


**Construction**  
Polyester Single Jacket Rubber Liner with Rubber Backing

**Temperature Range**  
-40° to 150°F (-40° to 65°C)

**Couplings**  
Aluminum or Brass NH/NST, IPT Threaded

**Approvals**  
Mine Safety & Health Administration (MSHA) Approval, No. 2G-15/1

**Colors**  
UNCOATED



**ALL-AMERICAN HOSE™**  
217 Titusville Road, Union City, PA 16438  
www.all-americanhose.com  
814.438.7616