



ATTACK



USA MADE



UL/ULC LISTED

8D

POLYESTER DOUBLE JACKET ATTACK HOSE

Our National Fire Hose 8D is a municipal grade double jacket hose with a lightweight EPDM rubber liner that meets all the requirements of NFPA 1961. It is designed for use as an attack handline hose and is manufactured to a service test pressure of 400 psi (2760 kPa) to handle all fireground challenges with ease.

FEATURES:

- Exceptional quality, double jacket, rubber lined municipal fire hose made from 100% high tensile strength ring-spun polyester yarn with a lining of extruded EPDM.
- Optional Dura-Cote™ treatment greatly increases abrasion, heat, flame and petrochemical resistance while virtually eliminating water pick-up. When treated, 8D is protected from mildew and no drying is required.
- Hose remains flexible to temperatures as low as -40°F (-40°C) and is highly resistant to ozone and oxidation.
- Manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system.

CONSTRUCTION

Polyester Double Jacket
EPDM Rubber Inner Liner

TEMPERATURE RANGE

-40°F to 150°F (-40°C to 65°C)

HOSE SIZING AND SPECIFICATIONS


SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (FOR 50' COUPLED)	FLAT WIDTH	BOWL SIZE	CERTIFICATION AVAILABLE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	IN	
1"	400 (2760)	800 (5515)	1200 (8275)	13 (5.9)	2.10"	1 1/2"	
1 1/2"	400 (2760)	800 (5515)	1200 (8275)	15 (6.8)	2.80"	1 15/16"	
1 3/4"	400 (2760)	800 (5515)	1200 (8275)	16 (7.3)	3.20"	2 1/8"	UL, ULC
2"	400 (2760)	800 (5515)	1200 (8275)	20 (9.1)	3.70"	2 1/2"	
2 1/2"	400 (2760)	800 (5515)	1200 (8275)	27 (12.2)	4.50"	3"	UL, ULC
3"	400 (2760)	800 (5515)	1200 (8275)	33 (15)	5.30"	3 5/16"	

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

HOW TO ORDER


TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL	OPTIONS
8D	10 = 1" 15 = 1 1/2" 17 = 1 3/4" 20 = 2" 25 = 2 1/2" 30 = 3"	X	50 = 50' 100 = 100'	Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White (coated) W = White (uncoated)	10 = 1" 15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3"	N = NH I = IPT	Aluminum	UL = UL Labeled ULC = UL Canada Labeled

Part No. Example: 8D17X50B15N = 8D Hose, 1 3/4" ID by 50' Length, Blue, 1 1/2" NH/NST Aluminum Coupling



NATIONAL FIRE HOSE

EPDM Rubber Liner
Polyester Inner Jacket
Polyester Outer Jacket



COUPLINGS

Aluminum NH/NST or IPT Threaded

COLORS

