



ATTACK



SUPPLY



USA MADE

ATX

HIGH PRESSURE NITRILE RUBBER ATTACK/SUPPLY HOSE

Manufactured in a similar process as TPX, ATX utilizes a 3-ply design where the cover and liner are extruded independently and double vulcanized to guarantee a consistent, compact hose wall. The polyester reinforcement can then be woven tighter, making this hose more resistant to puncture while also being easier to pack and store. ATX has a stronger jacket which increases the service test pressure of the LDH sizes to 300 psi (2070 kPa).

FEATURES:

- 3-ply rubber municipal fire hose with both the cover and liner made of heavy duty nitrile rubber, high tensile strength tightly woven polyester reinforcement for maximum durability and flexibility.
- Smooth liner keeps friction loss to a minimum.
- Nitrile rubber cover greatly increases abrasion resistance, provides long service life and the tightly woven reinforcement resists puncture.
- Remains flexible to temperatures as low as -5°F (-20°C) and is resistant to ozone, oxidation and most chemicals and petrochemicals.
- Suitable for high pressure attack, supply and relay applications.
- Suitable for pumping to sprinklers and standpipes, industrial firefighting and supplying aerial devices.
- Manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system.

HOSE SIZING AND SPECIFICATIONS

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (FOR 50' COUPLED)	FLAT WIDTH	BOWL SIZE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	IN
4"	300 (2070)	600 (4140)	900 (6200)	60 (27.2)	7.00"	4 ⁷ / ₁₆ "
5"	300 (2070)	600 (4140)	900 (6200)	84 (38.1)	8.75"	5 ⁵ / ₁₆ "
6"	300 (2070)	600 (4140)	900 (6200)	98 (44.5)*	10.25"	6 ³ / ₄ "

*Weight uncoupled.

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

HOW TO ORDER

TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
ATX	40 = 4" 50 = 5" 60 = 6"	X	50 = 50' 100 = 100'	Y = Yellow R = Red O = Orange	40 = 4" 50 = 5" 60 = 6"	N = NH I = IPT S = Storz	Aluminum


Part No. Example: ATX40X50Y40S = ATX Hose, 4" ID by 50' Length, Yellow, 4" Storz Aluminum Coupling



Nitrile Rubber Liner

Polyester Inner Jacket

Nitrile Rubber Outer Cover



CONSTRUCTION

3-Ply Nitrile Rubber Cover/Liner
Polyester Reinforcement

TEMPERATURE RANGE

-5°F to 200°F (-20°C to 93°C)

COUPLINGS

Aluminum NH/NST or IPT Threaded & Aluminum Storz

COLORS

Yellow

Red

Orange



ALL-AMERICAN HOSE™

all-americanhose.com | 814-438-7616 | 217 Titusville Road, Union City, PA 16438 USA