



ALL-AMERICAN HOSE™

217 Titusville Rd.
Union City, PA 16438

Irrigation Hose

All American Hose is a world class distributor of Lay Flat Hose

Hose Construction – 100% high tenacity yarn, extruded with thru the weave polyurethane construction. Liner and Cover minimum 3000 psi tensile strength.

Chemical Resistance – Hose capable of withstanding exposure to most hydro-carbons, gasoline, oils, alkalis and grease with no effect on the performance of the hose.

Ozone Resistance – The hose shows no visible signs of cracking of the liner or cover when subjected to testing in accordance with ASTM D1149-64, 100 PPHM/122°F/70 hours.

Abrasion Resistance – Abrasion resistance shall be 5X that of conventional rubber hose, 300,000 cycles on a Taber abrasion tester without exposure of the jacket.

Temperature Range - - 60°F (-51°C) to 180°F(82°C)

NSF standard 61 and potable water approved materials

Designed for maximum service life and low operating cost.

Fast deployment and retrieval – saving time and money

Easy to store and transport

Standard length – 660' (200M), 330'

Color – Blue

Manufactured within our ISO-9001 certified quality assurance system

Performance Chart

| Product | Inside Diameter (in) | Wall Thickness (in) | Average Weight (lbs. /ft.) | Working Pressure (psi) | Burst (psi) |
|---------|----------------------|---------------------|----------------------------|------------------------|-------------|
| IR30 | 3" | .130 | .60 | 200 | 700 |
| IR40 | 4" | .130 | .80 | 150 | 500 |
| IR45 | 4 1/2" | .130 | .94 | 150 | 500 |