



ALL-AMERICAN HOSE™

217 Titusville Rd.
Union City, PA 16438

TS – Agricultural Products – Sludge Hose
All-American Hose is a world class distributor of Lay Flat Hose
Hose Construction – 100% high tenacity yarn, extruded with thru-the-weave polyurethane construction.
Chemical Resistance – Hose must be capable of withstanding exposure to most hydro-carbons, gasoline, oils, alkalis and grease with no effect on the performance of the hose.
Ozone Resistance – The hose shall show no visible signs of cracking of the liner or cover when subjected to testing in accordance with ASTM D1149-64, 100 PPHM/122°F/70 hours
Abrasion Resistance – Abrasion resistance shall be 5X that of conventional rubber hose, 300,000 cycles on a Taber abrasion tester without exposure of the jacket.
Designed for maximum service life and low operating cost.
Fast deployment and retrieval – saving time and money
Easy to store and transport
Standard length – 660' (200M), shorter lengths available
Color – High Visibility Green (TS45, TS50, TS55, TS60)
Manufactured within our ISO-9001: 2015 certified quality assurance system

Performance Chart					
Product	Inside Diameter	Wall Thickness	Weight Lbs./Ft	Burst Pressure, PSI	Tensile Strength, Lbs.
TS45	4.5"	.150"	0.98	500	31,000
TS50	5"	.160"	1.14	500	35,100
TS55	5.5"	.170"	1.31	500	44,000
TS60	6"	.170	1.47	600	41,616

06/18