



ALL-AMERICAN HOSE™

217 Titusville Rd.  
Union City, PA 16438

<b>Agricultural Products – Sludge Hose</b>
<b>All American Hose is a world class distributor of Lay Flat Hose</b>
<b>Hose Construction</b> – 100% high tenacity yarn, extruded with thru the weave polyurethane construction. Liner and Cover minimum 3000 psi tensile strength.
<b>Chemical Resistance</b> – Hose must be capable of withstanding exposure to most hydro-carbons, gasoline, oils, alkalis and grease with no effect on the performance of the hose.
<b>Ozone Resistance</b> – The hose shall show no visible signs of cracking of the liner or cover when subjected to testing in accordance with ASTM D1149-64, 100 PPHM/122°F/70 hours
<b>Abrasion Resistance</b> – Abrasion resistance shall be 5X that of conventional rubber hose, 300,000 cycles on a Taber abrasion tester without exposure of the jacket.
<b>Designed for maximum service life and low operating cost.</b>
<b>Fast deployment and retrieval – saving time and money</b>
<b>Easy to store and transport</b>
<b>Standard length</b> – 660' (200M), shorter lengths available
<b>Color</b> – High Visibility Green (TS45, TS50, TS55) Brown (TSX60)
<b>Manufactured within our ISO-9001 certified quality assurance system</b>

<b>Performance Chart</b>					
Product	Inside Diameter	Wall Thickness	Weight Lbs./Ft	Burst Pressure, PSI	Tensile Strength, Lbs.
TS45	4.5"	.150"	0.98	500	31,000
TS50	5"	.160"	1.14	500	35,100
TS55	5.5"	.170"	1.31	500	44,000
TSX60	6"	.200	1.90	900	42,500

3/16

All-American Hose, LLC.

ISO 9001 Certified Quality Management System