



FIRE ENGINE BOOSTER HOSE

FIRE ENGINE BOOSTER HOSE: REELED AND READY FOR DUTY

Service ready on the reel, Fire Engine Booster Hose is the rugged frontline attack hose that knocks down fires fast. Designed for high-performance reliability from structure fires to forest blazes, the multiple aramid braid reinforced red reel hose features a specially compounded Ethylene Propylene Diene Monomer (EPDM) tough cover that resists abrasion and weathering. Inside, a smooth black synthetic EPDM rubber inner tube adds flexibility and sure, high-power flow. Available with Barway or external crimped steel couplings.



FEATURES:

- EPDM rubber fire hose is reinforced with high tensile aramid yarn, and smooth inner lining for exceptional strength, durability and flow.
- EPDM rubber compound provides a durable, flexible cover that resists abrasion, gouging, ultra-violet and ozone damage, as well as most chemicals.
- A smooth outer cover lowers drag resistance for sure serviceability.
- Fully loaded, ready on reel, multi-purpose frontline attack hose, handles structure and vehicle firefighting; grass, wildland and forestry fires; and industrial applications.
- Offers 4:1 safety factor (1" and ¾" only – 1½" has a 3:1 safety factor).
- Assembled in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system.
- Five year warranty.

HOSE SIZING AND SPECIFICATIONS

| SIZE | WORKING PRESSURE | BURST | WEIGHT (FOR 50' COUPLED) | WEIGHT (FOR 100' COUPLED) | BOWL SIZE |
|------|------------------|--------------|--------------------------|---------------------------|-----------|
| IN | PSI (kPa) | PSI (kPa) | LBS (KG) | LBS (KG) | IN |
| ¾" | 800 (5155) | 3200 (22060) | 21 (9.5) | 42 (19) | 1¼" |
| 1" | 800 (5155) | 3200 (22060) | 30 (13.6) | 60 (27.2) | 1½" |
| 1½" | 200 (1380) | 600 (4140) | 50 (22.7) | 100 (45.4) | 2" |

Note: 1.5" has a 3:1 Safety Factor.

Minimum Bend Radius ¾" = 7" and 1" = 8".

COLORS Red